



Parameters

Product name	Tripod Turnstile
Model	DR.TD.6380X
Cabinet material	SUS304 brushed stainless steel
Size	1200*280*1000 mm
Voltage	AC110V/AC220V±10% 50-60Hz
Driving motor	Solenoid Valve
Direction of passing	Uni-directional/Bi-directional
Passing width	≤550mm
Working environment	Indoor/outdoor, -15℃~60℃
Relative humidity	≤90%, no condensation
Opening speed	Fastest 1.5s, adjustable
Passing speed	20 people/min
MCBF	3 million times
Noise	<50dB
Communication interface	Level/Pulse/RS485 and TCP/IP
Input interface	Dry contact
IP level	IP54

Application

Office and administrative buildings
Ministries and public buildings
Banks and financial institutions
Industrial installations
Residential areas
Schools, colleges and universities

Functions

- ① Adopted a unique incomplete gear transmission system, so that the lock at zero, unlock more accurate and reliable;
- ② The whole system runs smoothly with low noise;
- ③ With a variety of working modes to choose from, you can two-way card reading, also can read the card, the other direction is prohibited, while reading the card, the other direction free passage, and the working mode of the gate can be set through the motherboard menu;
- ④ It has the function of power down rod and power up rod manually;
- ⑤ Support remote control of switch opening, power down and pole down functions to meet the special needs of users and fire safety requirements;
- ⑥ It has a unified and standard external electrical interface, which can be connected with various reading and writing equipment to facilitate system integration, and can realize remote control and management through management computer;
- ⑦ can be automatically on the traffic direction of the number of statistics, and displayed on the LCD screen, so that the manager of a certain direction of the number of traffic at the palm of his hand.
- ⑧ a clear direction of traffic indication function, with intuitive LED traffic indicator can be passed or prohibited.
- ⑨ It has the function of reading card with memory and without memory, and users can set it according to their needs through the motherboard keyboard.
- ⑩ It has the function of automatic reset. When the card is read, the passer does not pass within the specified time, the system will automatically cancel the passer's access authority, and the limited time can be set by the management personnel.
- ⑪ Anti electric shock:

All electric modules are designed to operate under the safety voltage of 24V, and configured with residual current protective device to avoid electric shocks.

Emergency escape function:

Equipped with emergency escape control device, the arm will drop down automatically so as to form an open passageway to evacuate people.

Dimension

